

Specifications

BTUHD-30 -Hi 30,000
 Lo 19,900
 D-40 -Hi 40,000
 Lo 6,500

EfficiencyThermal up to 86.4%

Gas SupplyNatural or LP

Pilot SystemPiezo Spark

Safety ControlsANSI/AGA
 Certified

Safety TestedWarnock Hersey
 to CGA/AGA/ANSI Std.

Shipping Weight ...D-30 -175 lbs.
 D-40 -200 lbs.

Products, specifications, and prices
 subject to change without notice

Consult our Owners Manual for all final dimensions.
 Menota products are manufactured in the U.S.A.



Standard Equipment

Log set, log rack, coal bed, D-30:
 2-level burner, D-40: 3-level
 burner, 2 blowers with rheostat,
 neo-ceram glass and firebrick.

Options

Black, black onyx, vintage iron,
 cast, copper, nickel, silver, brass,
 and 24k gold fronts; wall switch,
 remote control and thermostat.

Rectangular or arched surround.
 Brass or black surround trim.

Custom surrounds available upon
 request. Co-linear or co-axial flue
 venting. Natural vent (B-Vent),
 D-30 only.

	D-30 TimberFire			D-40 Deep Timber		
A	24"	27"	31"	31"	33"	36"
B	36"	40"	44"	44"	48"	52"
C	30 7/16"			*34 7/8" **34"		
D	22 1/4"			24 1/4"		
E	16 3/8"			16 13/16"		
F	1 1/8"			1 1/8"		
G	19"			23"		
H	30 7/16"			36 1/2"		
I	15 1/2"			19 1/8"		
J	8 3/8"			9"		

*With no Surround Trim or with the Standard Surround Trim C=34 7/8".

**With the Optional Deeper Surround Trim C=33 3/4"

D-30 Andover Arched Faceplate

L-24 7/8" M-40 1/4" N-28 7/8" RADIUS-52 11/32"

D-30 Bentley Arched Faceplate

L-28 7/8" M-40 1/4" N-22 7/8" RADIUS-36 7/8"

D-40 Andover & Bentley Arched Faceplate

L-28 3/8" M-44 3/16" N-33 3/8" RADIUS-51 1/2"

